



Technical Data Sheet

UniPak Standard Lid 69 mm

Logical no: 2900

Dimensions

Shape: Round
External diameter: 67,4 mm +/- 0,3 mm
Height: 6,4 mm +/- mm

Closure type

Closure type: Snap-On
Lid type: Standard

Decoration

Decoration available: IML
Decoration area offset: NA mm

Raw material

Raw material options: PP
Masterbatch colours: Colours according to RPC Superfos standard selected pantone colours.

Hot filling: The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures

Cold temperatures: Freezing conditions require special resins available on request. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures

Weight

Weight: 2,5 g +/- g

Packing

On pallet 1200x800:	120384 pcs.	On pallet 800x1200	60192 pcs.
Number per box:	5016 pcs.	Number per box:	5016 pcs.
Boxes per pallet:	24 pcs.	Boxes per pallet:	12 pcs.
Height incl. pallet:	2,13 m	Height incl. pallet:	1,15 m
Stackability, empty:	2 pallets high	Stackability, empty:	NA pallets high

Quality Specifications

Approvals: All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

Shelf life: The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period

Quality information: Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

Other

UN approval: No

Special:

Specifications are subject to change without notice.

Version 10.1

Latest revision : 29-08-2014

